

GAS - 90 Degree Elbow (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG12015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - 45 Degree Elbow (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG21015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - 90 Degree Street Elbow (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG12S015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12S022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12S028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12S035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12S042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG12S054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - 45 Degree Street Elbow (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG21S015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21S022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21S028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21S035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21S042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG21S054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - Male Iron Adaptor (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size A (mm)	Size B (inch)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG3015	15	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3015020	15	3/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3022015	22	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3022	22	3/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3028	28	1"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3035	35	1.1/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3042	42	1.1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG3054	54	2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - Female Iron Adaptor (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size A (mm)	Size B (inch)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG2015	15	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG2022	22	3/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG2028	28	1"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG2035	35	1.1/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG2042	42	1.1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG2054	54	2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - Stop End (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG61015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG61022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG61028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG61035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG61042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG61054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓

GAS - Insert Reducer (M-Profile with Yellow HNBR O-Ring)



Dimensions: **Same as water fitting**

Product Code	Size A (mm)	Size B (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG6022015	22	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6028015	28	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6028022	28	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6035022	35	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6035028	35	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6042022	42	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6042028	42	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6042035	42	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6054035	54	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG6054042	54	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓



GAS - Coupling (M-Profile with Yellow HNBR O-Ring)

Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG1015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓



GAS - Reducing Coupling (M-Profile with Yellow HNBR O-Ring)

Dimensions: **Available on Request**


Product Code	Size A (mm)	Size B (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG1R022015	22	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG1R028022	28	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓



GAS - Equal Tee (M-Profile with Yellow HNBR O-Ring)

Dimensions: **Same as water fitting**

Product Code	Size (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG24015	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG24022	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG24028	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG24035	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG24042	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG24054	54	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓



GAS - Reducing Branch Tee (M-Profile with Yellow HNBR O-Ring)

Dimensions: **Same as water fitting**

Product Code	Size A (mm)	Size B (mm)	Size C (mm)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG25022015	22	22	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25028015	28	28	15	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25028022	28	28	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25035022	35	35	22	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25035028	35	35	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25042028	42	42	28	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25042035	42	42	35	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG25054042	54	54	42	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓



GAS - Female Branch Tee (M-Profile with Yellow HNBR O-Ring)

Dimensions: **Same as water fitting**

Product Code	Size A (mm)	Size B (mm)	Size C (inch)	Working Temperature (°C)	Max Pressure (Bar)	Gas Approved	Kitemarked	ISO 9001 ISO 14001
CCPG30015	15	15	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG30022015	22	22	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG30022020	22	22	3/4"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓
CCPG30028015	28	28	1/2"	-20 to 70	5 Outdoors or 1 Indoor	✓	✓	✓