

## CORE Inhibitor



Prevents system corrosion and limescale deposits. Protects bare metal surfaces & contributes to longer system life. Contains buffer to maintain neutral system water pH.

# CORE® Chemicals

## CORE Biocide

Designed to prevent the formation and growth of bacterial contamination, algae & microorganisms.

Contains **two** active ingredients, making it more efficient than single biocidal treatments.



**VIEW THE FULL RANGE**



# Core values, quality products



View & download our **Technical Documents**



Order online  
[sbsonline.net/CORE](http://sbsonline.net/CORE)



View the tutorial  
[youtube.com](http://youtube.com)

**Don't forget to order the Insulation Jacket!**  
**Available on request**

# sbscore.co.uk



Follow our LinkedIn page **CORE by SBS**

The information within this document is believed to be correct at the time of publication; however, the document is for guideline use only. For complete accuracy, always check the product with a CORE representative. Missing information was either not available or disclosed. It is your responsibility that any product meets the necessary requirements. Any reliance placed upon this information will be totally at the user's risk.

# CORE®

## Side Stream Magnetic Filter Range



Compliant  
BG29 and BG50



Exclusively distributed by



# Standard Side Stream

# Side Stream PLUS

# Side Stream XL



## For light commercial applications

<b>Product Code:</b>	CORESSFIL
<b>Body Material:</b>	SS304
<b>Inlet &amp; Outlet Pipe:</b>	1"
<b>Non-Ferrous Filtration Method:</b>	Reusable stainless steel mesh basket
<b>Max Operating Pressure:</b>	6 Bar
<b>Max Operating Temp:</b>	90°C
<b>Max Flow Rate:</b>	100 l/min
<b>Litre Capacity:</b>	6 litres
<b>Magnet Type:</b>	Single "Easy Clean" Rod

## For larger commercial applications

<b>Product Code:</b>	CORESSFP
<b>Body Material:</b>	SS304
<b>Inlet &amp; Outlet Pipe:</b>	1"
<b>Non-Ferrous Filtration Method:</b>	Reusable stainless steel mesh basket
<b>Max Operating Pressure:</b>	10 Bar
<b>Max Operating Temp:</b>	90°C
<b>Max Flow Rate:</b>	100 l/min
<b>Litre Capacity:</b>	13 litres
<b>Magnet Type:</b>	Single "Easy Clean" Rod

## For industrial applications

<b>Product Code:</b>	CORESSFXL
<b>Body Material:</b>	SS304
<b>Inlet &amp; Outlet Pipe:</b>	2"
<b>Non-Ferrous Filtration Method:</b>	Reusable stainless steel mesh basket
<b>Max Operating Pressure:</b>	16 Bar
<b>Max Operating Temp:</b>	90°C
<b>Max Flow Rate:</b>	230 l/min
<b>Litre Capacity:</b>	24 litres
<b>Magnet Type:</b>	Two "Easy Clean" Rods