CORE 32 TBV Product Selector



	CORE TBV	Albion 32 TBV	Reliance TREG TBV	Altecnic 116 TBV	BOSS 206TD TBV
MPN	CORETBV32015	AATBV32050	TREG100060	116240	20520023
	CORETBV32020	AATBV32075	TREG100065	116250	20520034
	CORETBV32025	AATBV32100	Sharkbite version	116260	20520045
Connections	Female Bsp	Female Bsp	Female Bsp/Sharkbite	Female Bsp	Female Bsp
Temperature Gauge	Included	Included	Included	Optional	Included
Material	DZR Brass CW602N	DZR Brass CW602N	DZR Brass	DZR Brass CW724R (Low Lead)	DZR Brass CW724R (Low Lead)
Approvals	WRAS	WRAS	WRAS	WRAS	WRAS
Anti Legionella Temp	70°C	70°C	70°C	70°C	70°C
Max Inlet Pressure	25 Bar (static)	25 Bar (static)	10 Bar (working)	16 Bar (working)	16 Bar (working)
Working Temp Range	40°C to 60°C	40°C to 60°C	40°C to 65°C	35°C to 60°C	35°C to 60°C
Max Temp	90°C	90°C	Not Stated	90°C	90°C
Other			Pre-Insulated	Removable Cartridge	Removable Cartridge





Disclaimer: The information within this document is believed to be correct at the time of publication; however, the document is for guideline use only. For complete accuracy, always check the product with a CORE representative. Missing information was either not available or disclosed. It is your responsibility that any product meets the necessary requirements. Any reliance placed upon this information will be totally at the user's risk.