

Brass Binder Test Plugs Data Sheet

Large Extended Plug



15mm (1/2") BSPT
Type EP15EX

Small Extended Plug



8mm (1/4") BSPT
Type EP8EX

Large Test Plug



15mm (1/2") BSPT
Type EP15

Small Test Plug



8mm (1/4") BSPT
Type EP8

Thread: 15mm (1/2") BSPT	Thread: 8mm (1/4") BSPT
O/A Length inc. Cap: 40mm / Extended Plug 78mm	O/A Length inc. Cap: 38mm / Extended Plug 75mm
Max. Probe dia: 4mm	Max. Probe dia: 4mm

* Additional colour straps are available upon request, (Red & Blue indicate hot and cold water)

- **The extended plugs give approximately an extra 38.10mm (1 1/2") for insulation**

Other lengths available to order. Add to type number in mm - **Example: EP 15 EX + 20mm**

- **Standard Construction Types EP8 EP8EX EP15 EP15EX**

- Body, cap and retaining ring: Brass
- Cap seal: Neoprene Rubber
- Retaining strap: Ethylene Propylene Rubber
- Core: Ethylene Propylene Rubber
- Max. Pressure: 35 BAR, 500 PSI
- Temp range: -10°C up to +120°C
- Suitable for low temperature hot water, chilled water and low temperature steam

- **Suitable For Some Oils, Gases and Other Fluids**

- **Safety**

Binder Test Plugs and accessories are not recommended to be used on medium or high temperature hot water systems. Ethylene Propylene rubber is suitable for temperatures up to 135°C however if Plugs are used with injurious liquids or gases protective clothing, i.e. long sleeved gloves, face and eye protection should be worn.

Disclaimer: The information within this document is believed to be correct at the time of publication; however, the document is for guideline use only. For complete accuracy, always check the product with an SBS representative. Missing information was either not available or disclosed. It is your responsibility that any product meets the necessary requirements. Any reliance placed upon this information will be totally at the user's risk.